



# VENTILATION SYSTEMS

---

## INSTALLATION INSTRUCTIONS





**QASAIR** rangehoods are made to suit Australian cooking conditions and traditions. **QASAIR** incorporates a system that is efficient over all modern-cooking appliances, while achieving unequalled level of quietness in the kitchen.

Now the latest cooking appliances including indoor barbecues, deep fryers, exotic wok appliances and high speed gas burners can be used in the design of the kitchen without the worry or fear of filling the house with grease, odours, steam or heat.





# CONTENTS

Important information	2
Instructions for Models FA / MI / UCH / UV / MC	5
Instructions for Models H Series & PYR	15
Instructions for Models 3Flare / CM / LCM / SE / ST / POY / MAJ / IN / STA	21
Instructions for Models TR-CT	35
Instructions for Models QR / BRH	37
Instructions for Models 4 Flare / MHR / VIS / PRE / DIPL / D400 / SQ420 / FPR / MA	41
Instructions for Special Models	50
Lamp Replacement	51
Ducting Pieces	52
Installation Ideas	69
Care & Maintenance	76
Warranty	77

# IMPORTANT information

QASAIR rangehoods are designed to remove all the by-products of cooking – heat, steam, grease and odours.

QASAIR ducting is designed to ensure optimum performance from your rangehood.

The installation of QASAIR rangehoods must comply with the information in this booklet.

Every QASAIR rangehood must be ducted to the outside atmosphere by the use of zinc-alume duct or non-porous and non-flammable materials. Rangehoods must not be vented into a wall cavity or a ceiling space. This prevents a build up of grease which can be a fire risk. Ensure the external outlet vent does not restrict the airflow in any way, as this may result in reduced performance.

The exhaust air must not be discharged into a flue which is used for exhausting fumes from appliances burning gas or other fuels.

**QASAIR rangehoods must be ducted in duct work equivalent to the outlet of the rangehood. ie. The cross sectional area of the rangehood outlet and the duct work must be equal. Do not reduce the duct size or have sharp bends. Enlarge the duct size if the duct is to run 6 metres or longer. Advice from QASAIR is available to ensure optimum performance.**

Always use non-flammable materials to minimise the risk of fire in the duct at a later date.

Avoid sharp bends.

Ensure all ducting pieces are correctly fitted and sealed with either duct tape or silicone to ensure that fumes do not escape into the ceiling space and seep into living areas through vents or light fittings.

The installation and fitting of the rangehood should be done in such a way that will allow the unit to be removed if service is required. Additional costs incurred in the removal of wall tiles, damage to walls or bench tops are not covered by warranty.

Always adequately ventilate the room when the rangehood is used at the same time as appliances burning gas or other fuels.

Gas regulations state that a QASAIR rangehood should be installed no less than 600mm above the trivet on a gas appliance. QASAIR recommend between 600 – 800mm depending on the model, for optimum performance. Check for local requirements in the area in case additional provisions apply.

**WARNING:** Incorrect venting will result in additional noise and a reduction in efficiency. Exhaust air must not be discharged into any chimney or flue, which may carry combustible products from other sources.

The rangehood is not intended for use by children or infirm persons without supervision. Children should be supervised to ensure that they do not misuse the appliance.

Do not flambé under the rangehood.

If the supply cord is damaged, an authorised service centre or licensed electrician must replace it.



DISTRIBUTED IN AUSTRALIA BY  
CONDARI PTY LTD

Tel: 1300 360 563

Tel: +61 3 9482 7088 Fax: +61 3 9482 7011

Email: sales@qasair.com.au

Website: www.qasair.com.au

YOUR DISTRIBUTORS

Australia

NSW	Tel: +61 2 9316 4599	Fax: +61 3 9316 9299
QLD	Tel: 0408 833 321	Fax: +61 7 3282 9122
WA	Tel: +61 8 9381 1188	Fax: +61 8 9381 6000
SA	Tel: 0419 109 256	Fax: +61 8 8449 6973
ACT	Tel: +61 2 6239 2877	Fax: +61 2 6239 2750
TAS	Tel: +61 3 6231 6633	Fax: +61 3 6231 6662
NT	Tel: +61 8 8947 3444	Fax: +61 8 8947 0419

New Zealand

Kitchen Appliance Specialist Ltd

320 Manchester Street

Christchurch New Zealand

Tel: +64 3 379 0360 Fax: +64 3 365 5623

Singapore

Eldric Marketing Pte Ltd

176 Orchard Road

#05-03 Centrepoint Singapore 238843

Tel: +65 6 339 1168 Fax: +65 6 733 8133

5 Pereira Road

#02-01 Asiawide Industrial Building

Singapore 238843

Tel: +65 6 743 8388 Fax: +65 6 743 0202

QASAIR RANGEHOODS MADE IN RINGWOOD 3134

QASAIR RESERVES THE RIGHT TO CHANGE SPECIFICATION WITHOUT NOTICE. © IS A REGISTERED TRADE MARK.

◆ For cleaning and polishing stainless steel rangehoods and kitchen appliances

◆ Perfect for all kitchen surfaces – stainless steel and laminated bench tops.

