

The Thermidor rangehood is designed to be built into the ceiling.

Installation instructions

1. Remove hood from packaging being careful not to touch the stainless steel front.
2. Locate centre of stove and using level or plumb line, mark centre line up to the ceiling.
3. In a new house the hood can be fixed into the ceiling space by bolting or screwing into the ceiling joists or by building a frame to support the hood.
4. In an existing home, a hole must be cut into the ceiling and pushing the hood into the space. Ensure there are no obstructions to placing the hood in position. In these cases a ceiling flange in stainless can be supplied to finish the hood to the ceiling. It is not supplied in colours.
5. The outlets are either top or back ducted and can be changed on site and the hood can be reversed to suit the intended ducting direction.
6. Once secure in position standard ducting pieces can be used.
7. Switches are not provided and remote switching in a convenient position must be installed. The switching used must be an electrically approved switch and is not provided by Condari Pty Ltd.

INSTRUCTIONS for models

TR-CT1000

TR-CT1200

TR-CT1500

Thermidor TR-CT

TR-CT-1000-3	Top or Back Ducted
TR-CT-1200-3	Top or Back Ducted
TR-CT-1500-3	Top or Back Ducted

- Duct outlet dimension 235 x 110mmw
- Standard triple motor ducting will fit
- Electrical – 10AMP junction box

